

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-201904

(43)Date of publication of application : 10.08.1990

(51)Int.Cl.

H01F 1/22

(21)Application number : 01-020287

(71)Applicant : HITACHI MAXELL LTD

(22)Date of filing : 30.01.1989

(72)Inventor : MARO TAKESHI
FUJIWARA HIDEO

(54) HIGH PERMEABILITY MATERIAL

(57)Abstract:

PURPOSE: To acquire a high permeability material of a large saturated flux density and a small deterioration at a high frequency region by using a magnetic material of a large electric resistivity where polymer is deposited between ferromagnetic metal particles.

CONSTITUTION: A polymer is deposited between ferromagnetic metal particles, saturated magnetization is made not less than 800G, and a resistivity is made $180\mu\Omega\text{-cm}$ or more.

Simultaneous vapor deposition of ferromagnetic metal and polymer realizes deposition of polymer between ferromagnetic metal particles and a soft magnetic film of a large electric resistance.

Simultaneous vacuum deposition makes it easy for the ferromagnetic metal to realize a column structure and a polymer deposits between the columns. Since a polymer of an insulator deposits between the columns, an electric resistance

increases in comparison with a simple substance of an original ferromagnetic metal. Thereby, an eddy current loss reduces, deterioration of permeability in a high frequency region is restrained, and a saturated flux density increases.

